

ABLOY® 南京錠



アブロイ南京錠はセキュリティを最重要視する多くの施設に選択されています。



欧州EN基準セキュリティグレード 南京錠 (建築金物) EN 12320

要件	1	2	3	4	5	6	
鍵違いの最低数	300	1000	2500	5000	10000	20000	
シャックル / ステープルの引張り	3	5	15	30	70	100	kN
シャックル / ステープルのねじり	40	100	200	450	1200	2500	Nm
シャックル / ステープルの切断	6	15	25	35	70	100	kN
シャックル / ステープルの破壊			1250×800 -20℃	3050×1000 -20℃	6550×1400 -40℃	7150×1500 -40℃	×5 times
ロック・ボディの破壊			1250×800 -20℃	3050×1000 -20℃	6550×1400 -40℃	7150×1500 -40℃	×5 times
シリンダー・プラグまたはロッキング・メカニズムへの負荷			4	5	10	15	kN
ドリリング (穴あけ)				2	4	8	min
のこ引き				2	4	8	min
シリンダー・プラグのトルク耐性 (回数)			5	15	20	30	Nm

MODEL						シャックル (mm)			シリンダータイプ			
寸法 (mm)	製品番号	EN セキュリティ グレード	素材						N プロテック	C クラシック	シリンダー取外し	
			ボディ	シャックル	仕上げ						可能	不可
	PL362	6	CHS	CHBS	クローム	15	25	30	●		●	
	PL350/25	5	CHS	CHBS	クローム	14	25	31	●		●	
	PL350/50	5	CHS	CHBS	クローム	14	50	31	●		●	
	PL342	4	CHS	CHBS	クローム	10	25	25	●		●	
	PL340/25	4	CHS	CHBS	クローム	10	25	28	●		●	
	PL340/50	4	CHS	CHBS	クローム	10	50	28	●		●	
	PL341/25	3	真鍮	CHBS	クローム	10	25	28	●		●	
	PL341/50	3	真鍮	CHBS	クローム	10	50	28	●		●	
	PL330/25	3	真鍮	CHBS	クローム	8	25	25	●		●	
	PL330/50	3	真鍮	CHBS	クローム	8	50	25	●		●	
	PL330/100	*	真鍮	CHBS	クローム	8	100	25	●		●	
	PL321/20	*	真鍮	ステンレス	クローム	5	20	18	●			●
	PL321/50	*	真鍮	ステンレス	クローム	5	50	18	●			●
	PL320/20	2	真鍮	ステンレス	クローム	5	20	18		●		●
	PL320/50	*	真鍮	ステンレス	クローム	5	50	18		●		●
	3020	2	真鍮	ステンレス	真鍮×クローム	7	35	26		●		●
	3021	*	真鍮	ステンレス	真鍮×クローム	7	76	33		●		●

* = 未試験 CHS = 硬化鋼 CHBS = 硬化ボロン鋼

ご発注の際は、下記事項をご確認ください。

● シリンダーのタイプをお選びください。

C: クラシック N: プロテック

● シャックルの高さ (20、25、50、100mm)

● シリンダーの取り外し可能／不可能。

● キータイプ (同一キー “KA” およびマスターキー “MK” の場合)
マスターキーをご希望の場合はプロテックタイプになります。



アブロイ 日本代理店
共栄工業株式会社

〒140-0013 東京都品川区南大井3-28-15

Tel.03-3762-1235

Fax.03-3762-1351

www.kyoeiabloy.jp

An ASSA ABLOY Group company

ASSA ABLOY

Abloy Oy is one of the leading manufacturers of locks, locking systems and architectural hardware and the world's leading developer of products in the field of electromechanical locking technology.

The ASSA ABLOY Group is the world's leading manufacturer and supplier of locking solutions, dedicated to satisfying end-user needs for security, safety and convenience.